PRODUCT SAFETY DATA SHEET

Canon Production Printing Netherlands B.V.

Van der Grintenstraat 10

P.O. Box 101 5914 HH Venlo The Netherlands telephone +31 77 359 2222



Number: EN-HYB370-380c-HQ Date: December 2019

For safety questions contact the Product Safety Coordinator of your local sales and service organisation

| Product Name(s) Model(s) | Arizona 1340 GT, Arizona 1360 GT, Arizona 1380 GT, Arizona 1340 XT, Arizona 1360 XT, Arizona 1380 XT all with option RMO HYB370 and HYB380 Flatbed digital color print system Canon Arizona® 13x0 GT up to 33,6 m²/h and Canon Arizona® 13x0 XT up to 35,0 m²/h Option RMO - Roll Media Printing Up to 25,6 m²/h | |
|---|---|--|
| Description Process speed | | |
| Dimensions: * width * depth * height * weight | Arizona 13x0 GT 4656 mm 2000 mm (2285 mm with RMO) Table 888 mm and Gantry 1300 mm 856 kg, with RMO 1106 kg | Arizona 13x0 XT 4656 mm 3830 mm (4120 mm with RMO) Table 888 mm and Gantry 1300 mm 1625 kg, with RMO 1800 kg |
| Electrical data: * voltage * current-rated * building fuse Mains connection Safety class Protection class EMC Class Safety certification Battery Type (weight) | Arizona 13x0 GT 200 – 240 V 50/60Hz 8 A Inlet 1 and 3 A Inlet 2 20 A USA and 16 A EU Cable with plug I (IEC 61140) Protective earth connection IP2X (IEC 60529) Class A (according to EN61000-6-4) According to 2006/42/EC BG-listed (DP 18067), UL73 and CSA 22.2 No. 68 BR2032 (3,3 grams, present on CPU) | |
| Energy consumption: * off * ready * maximum | Arizona 13x0 GT 0 W 200 W 1700 W Inlet 1 and 500 W Inlet 2 | Arizona 13x0 XT 0 W 200 W 3450 W Inlet 1 and 500 W Inlet 2 |
| Noise emission ¹ : * Sound pressure level (at operator position) Heat emission Radio interference Radiation Chemical emission: * dust * ozone * TVOC | $L_{pA} \ less \ than \ 70 \ dB \ (A)$ Not applicable Complies with Directive 2004/108/EC and FCC rules and regulations, part 15 Class A. Not applicable Emission (mg/h) | |
| Recommended room ventilation | ≥ 1200 m³ per hour. For heat evacuation extra ventilation may be necessary. | |
| Consumables | This apparatus is suitable for IJC357 Ink Materials | |
| Additional safety information | UV inks can be harmful if not properly handled. Follow the guidelines in the User Guide carefully in order to ensure maximum safety. | |

¹ average concentration, additional to background, calculated for a daily volume of continuous prints during a work time of 8 h at recommended minimal room volume and room ventilation *Under normal conditions of use concentrations are considered to remain around or below above concentrations. Concentrations are a best estimate and have been calculated from concentration measurements performed under practical conditions in a room with a volume of 195 m³ and a ventilation rate of 6/h.*





Approval according to Machinery Directive 2006/42/EC



Approval according to standard UL73 and CSA 22.2 No. 68

US



²Report available on request.

Approved according

This safety data sheet has been compiled to the best of our knowledge as a compact guide to safe handling of this product. We reserve the right to revise safety data sheets as new information becomes available. It is the user's responsibility to determine the suitability of this information for the adoption of safety precautions as may be necessary and to contact the company to make sure that this sheet is the latest one issued. If and in so far as limitation of liability is permitted under the applicable laws, we do not accept liability for any inaccuracy that may occur in this information.