



SPECIFICATION

P/N:OP-2LSM7015-3 0.72W

100
LM/W




Application:

- 3D illumination LED letters with Depth 60-200MM
- Light box with Depth 60-200MM


Features:

- Aluminum PCB
- Light decay <3% for 6000hrs
- CRI>70
- 3-step MacAdam ellipse
- V2 fire safety level
- IP65 waterproof
- Cuttable every module
- 3 years warranty

Beam Angle:160°





Dimensions:




Order INFO and Parameter:

Part No.	Voltage	Power/pc	Lumen/pcs	LED Type	Ra	Housing material	Dimension	Working TEMP	Available Color
OP-2LSM7015-3	DC12V	0.72W	75LM	SMD2835	>70	PVC	70*14.8*7.1mm	-25°C to +60 °C	

Installation Reference:



Depth(H)	Dx	Dy	Qty/m ²	Power/m ²	Illumination
90MM	120MM	120MM	64PCS	46W	3060LUX
100MM	140MM	140MM	49PCS	35W	2360LUX
120MM	160MM	160MM	36PCS	26W	1760LUX
150MM	200MM	200MM	25PCS	18W	1080LUX



Packing Details:

Packing	Qty/chain	Qty/bag	Qty/carton	Carton Size
Qty	20pcs	200pcs	2000pcs	45*31*29cm
Weight	0.18KG	1.8KG	19.5KG	