A CANON COMPANY

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

UVgel 460 ink Black

of the mixture

Other means of identification

Article Number 1070104731

Registration number

None. Synonyms

1965C041AA **Product code** 15-March-2019 Issue date

Version number 13

27-September-2019 **Revision date** Supersedes date 21-June-2019

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Inkjet printing ink.

Uses advised against Other uses not recommended.

1.3. Details of the supplier of the safety data sheet

Océ-Technologies B.V. Supplier **Address** St. Urbanusweg 43 City 5914 CA Venlo The Netherlands Country +31 77 359 2222 **Telephone Number** sds-hq@oce.com E-mail address

1.4. Emergency telephone number

National Poison 111 (Available 24 hours a day.)

Information Center

+44 (0) 1235 239 670 For chemical emergencies only. (Available 24 hours a **NCEC Service**

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin corrosion/irritation Category 2 H315 - Causes skin irritation. Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Skin sensitisation Category 1 H317 - May cause an allergic skin

reaction.

Reproductive toxicity Category 1B H360 - May damage fertility or the

unborn child.

Environmental hazards

Hazardous to the aquatic environment, Category 2 H411 - Toxic to aquatic life with

long-term aquatic hazard long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: (5-Ethyl-1,3-dioxan-5-yl)methyl acrylate, 2-Propenoic acid, 1,6-hexanediyl ester, polymer with

2-aminoethanol, Ethyl 4-dimethylaminobenzoate, PROPOXYLATED NEOPENTYL GLYCOL

DIACRYLATE

1965C041AA Version #: 1.3 Revision date: 27-September-2019 Issue date: 15-March-2019

Hazard pictograms



Danger Signal word

Hazard statements

Causes skin irritation. H315

May cause an allergic skin reaction. H317 Causes serious eye irritation. H319

May damage fertility or the unborn child. H360 Toxic to aquatic life with long lasting effects. H411

Precautionary statements

Prevention

Avoid release to the environment. P273

Wear protective gloves/protective clothing/eye protection/face protection. P280

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present P305 + P351 + P338

and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention. P308 + P313 If skin irritation or rash occurs: Get medical advice/attention. P333 + P313

Not available. Storage Disposal Not available.

Supplemental label information None.

2.3. Other hazards Not a PBT or vPvB substance or mixture.

Chronic 1;H410

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General	info		
General	Into	rmat	ıon

Chemical name		%	CAS-NO. / EC NO.	REACH Registration No.	Index No.	Notes
(5-Ethyl-1,3-dioxan-5-yl)n acrylate	nethyl	40 - < 70	66492-51-1 266-380-7	01-2119976303-36-XXXX	-	
Classification:	Skin Irrit. 2	2;H315, Skin S	ens. 1B;H317, Aqu	atic Chronic 2;H411		
PROPOXYLATED NEOP GLYCOL DIACRYLATE	ENTYL	5 - <10	84170-74-1 -	01-2119970213-43-xxxx	-	
Classification:	Skin Sens	. 1B;H317, Aq	uatic Chronic 2;H4	11		
2-Propenoic acid, 1,6-hex ester, polymer with 2-ami		1 - < 5	67906-98-3 -	-	-	
Classification:	Skin Irrit. 2	2;H315, Skin S	ens. 1;H317, Eye I	rrit. 2;H319		
Ethyl 4-dimethylaminober	nzoate	1 - < 5	10287-53-3 233-634-3	01-2120766020-67-xxxx	-	
Classification:	Repr. 1B;I	H360, Aquatic	Chronic 2;H411			
Alcohol		1 - <3	Proprietary	-	-	
Classification:	Eye Irrit. 2	;H319	_			
Trimethylolpropane triacry	ylate	1 - <3	15625-89-5 239-701-3	-	607-111-00-9	
Classification:	Skin Irrit. 2 Chronic 1:		ens. 1;H317, Eye I	rrit. 2;H319, Aquatic Acute 1;	H400, Aquatic	
Carbon Black		1 - <2.5	1333-86-4 215-609-9	01-2119384822-32-xxxx	-	
Classification:	-					
DI(TRIMETHYLOLPROP TETRAACRYLATE	ANE)	1 - <2.5	94108-97-1 302-434-9	01-2119977121-41-XXXX	-	
Classification:	Skin Sens	. 1;H317, Eye	Irrit. 2;H319, Aquat	ic Chronic 2;H411		
HEXAMETHYLENE DIAC (HDDA)	CRYLATE	< 1	13048-33-4 235-921-9	-	607-109-00-8	
Classification:	Skin Irrit.	2:H315. Skin S	ens. 1:H317. Fve I	rrit. 2;H319, Aquatic Acute 1;	H400. Aquatic	

Material name: UVgel 460 ink Black

SDS UK 1965C041AA Version #: 1.3 Revision date: 27-September-2019 Issue date: 15-March-2019

Chemical name % CAS-No. / EC No. REACH Registration No. **Notes** Index No.

Phenylbis(2,4,6-trimethylbenzoyl)

162881-26-7

01-2119489401-38-xxxx 015-189-00-5

phosphine-oxide

423-340-5

Classification: Skin Sens. 1;H317, Aquatic Chronic 4;H413

< 1

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First aid measures

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice General information

(show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in

attendance. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

4.2. Most important symptoms and effects, both acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear

appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be

contained. For personal protection, see section 8 of the SDS.

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the For emergency responders

SDS.

6.2. Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all

environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into

drains, water courses or onto the ground.

Material name: UVgel 460 ink Black

SDS LIK 1965C041AA Version #: 1.3 Revision date: 27-September-2019 Issue date: 15-March-2019

6.3. Methods and material for containment and cleaning up

Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s) Professional and Industrial

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	
Carbon Black (CAS 1333-86-4)	STEL	7 mg/m3	
	TWA	3.5 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

Workers

	Components	Value	Assessment factor	Notes
DI(TRIMETHYLOLPROPANE) TETRAACRYLATE (CAS 94108-97-1)				
	Long-term, Systemic, Dermal	1.67 mg/kg bw/day	300	Repeated dose toxicity
	Long-term, Systemic, Inhalation	5.88 mg/m3	75	Repeated dose toxicity

Predicted no effect concentrations (PNECs)

(= = = ,				
Components	Value	Assessment factor Notes		
DI(TRIMETHYLOLPROPANE) TETRA	ACRYLATE (CAS 94108-97-	1)		
Freshwater	0.001 mg/l	1000		
Marine water	0 mg/l	10000		
Sediment (freshwater)	0.484 mg/kg			
Sediment (marine water)	0.048 mg/kg			
Soil	0.096 mg/kg			
STP	100 mg/l	10		

8.2. Exposure controls

Appropriate engineering

Provide adequate ventilation. See operator manual or safety data sheet of the printer.

controls

Individual protection measures, such as personal protective equipment

General informationUse personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.: Ansell Microflex ® 93-260 (240 minutes)

Other Not normally needed. No special protective equipment required.

Respiratory protection Not required during normal intended use of this product.

Material name: UVgel 460 ink Black

Thermal hazards Not normally needed.

Hygiene measuresObserve any medical surveillance requirements. Always observe good personal hygiene

measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Contaminated work clothing should not be allowed out of the workplace.

Environmental exposure

controls

Contain spills and prevent releases and observe national regulations on emissions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Colour Black
Odour Very faint.
Odour threshold Not available.
pH Not applicable

Melting point/freezing point -34.34 °C (-29.82 °F) estimated

Initial boiling point and boiling

range

Not available

Flash point 139.0 °C (282.2 °F)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not applicable
Explosive limit - upper Not applicable

(%)

Vapour pressure< 70 mbar at 70 C</th>Vapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 300 °C (572 °F)

Decomposition temperature Not available.

Viscosity 190 - 250 mPa·s at 17 C

14.5 mPa·s at 70 C

Explosive properties Not explosive. **Oxidising properties** Not oxidising.

9.2. Other information

Density 1.07 g/cm3 at 70 C

1.11 g/cm3 at 25 C

VOC 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoidContact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous No hazardous decomposition products are known.

decomposition products

SECTION 11: Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

However, ingestion is not likely to be a primary route of occupational exposure. Not available. Ingestion

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred **Symptoms** vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components **Test Results**

(5-Ethyl-1,3-dioxan-5-yl)methyl acrylate (CAS 66492-51-1)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 2000 mg/kg

DI(TRIMETHYLOLPROPANE) TETRAACRYLATE (CAS 94108-97-1)

Acute

Dermal

LD50 Rat > 2000 mg/kg, 24 Hours

Inhalation

Vapour

LC50 Rat > 0.41 mg/l, 7 Hours Read across

Oral

LD50 Rat > 5000 mg/kg

Ethyl 4-dimethylaminobenzoate (CAS 10287-53-3)

Acute

Dermal

Solid

LD50 Rabbit > 2000 mg/kg bw/day

Oral

Solid

LD50

Rat > 2000 mg/kg bw/day

HEXAMETHYLENE DIACRYLATE (HDDA) (CAS 13048-33-4)

Acute

Dermal

LD50 Rabbit 3650 mg/kg, 24 Hours

Oral

LD50 Rat > 5000 mg/kg

Phenylbis(2,4,6-trimethylbenzoyl) phosphine-oxide (CAS 162881-26-7)

Acute

Dermal

LD50 Rat > 2000 ml/kg

Oral

LD50 Rat > 2000 mg/kg

PROPOXYLATED NEOPENTYL GLYCOL DIACRYLATE (CAS 84170-74-1)

Acute

Dermal

LD50 Rat > 2000 mg/kg, 24 Hours

Oral

LD50 Rat > 5000 mg/kg

Material name: UVgel 460 ink Black

SDS LIK 1965C041AA Version #: 1.3 Revision date: 27-September-2019 Issue date: 15-March-2019

Test Results Components **Species**

Trimethylolpropane triacrylate (CAS 15625-89-5)

Acute Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Irritation Corrosion - Skin

HEXAMETHYLENE DIACRYLATE (HDDA) **OECD 404**

Result: irritating Species: Rabbit

(5-Ethyl-1,3-dioxan-5-yl)methyl acrylate **OECD 404** Result: irritating

Species: Rat **OECD 404**

Trimethylolpropane triacrylate Result: irritating

Species: Rat **OECD 404**

PROPOXYLATED NEOPENTYL GLYCOL DIACRYLATE

Result: Not irritating

DI(TRIMETHYLOLPROPANE) TETRAACRYLATE **OECD 404**

Result: Not irritating Species: Rabbit

OECD 404 Ethyl 4-dimethylaminobenzoate

Result: Not irritating Species: Rabbit

Phenylbis(2,4,6-trimethylbenzoyl) phosphine-oxide

OECD 404 Result: Not irritating

Species: Rabbit

Serious eye damage/eye irritation

Causes serious eye irritation.

(5-Ethyl-1,3-dioxan-5-yl)methyl acrylate EU B,5

> Result: Not irritating Species: Rabbit

HEXAMETHYLENE DIACRYLATE (HDDA)

OECD 405 Result: irritating Species: Rabbit

PROPOXYLATED NEOPENTYL GLYCOL

OECD 405 DIACRYLATE Result: Not irritating

DI(TRIMETHYLOLPROPANE) TETRAACRYLATE

OECD 405 Result: Not irritating

Ethyl 4-dimethylaminobenzoate

Species: Rabbit **OECD 405** Result: Not irritating

Species: Rabbit **OECD 405**

Phenylbis(2,4,6-trimethylbenzoyl) phosphine-oxide

Result: Not irritating

Trimethylolpropane triacrylate

Species: Rabbit Result: irritating

Not a respiratory sensitizer. Respiratory sensitisation

Skin sensitisation May cause an allergic skin reaction.

Skin sensitisation

OECD 406 Ethyl 4-dimethylaminobenzoate

Result: Not sensitizing Species: Guinea pig

Phenylbis(2,4,6-trimethylbenzoyl) phosphine-oxide

OECD 406 Result: sensitising

Species: Guinea pig

PROPOXYLATED NEOPENTYL GLYCOL **DIACRYLATE**

OECD 406

Result: sensitising Species: Guinea pig OECD 406, GMPT

HEXAMETHYLENE DIACRYLATE (HDDA)

Result: sensitising Species: Guinea pig

DI(TRIMETHYLOLPROPANE) TETRAACRYLATE

OECD 429 Result: positive Species: Mouse

(5-Ethyl-1,3-dioxan-5-yl)methyl acrylate

OECD 429 Result: sensitising Severity: EC3=2,8%

Material name: UVgel 460 ink Black

SDS UK

Skin sensitisation

PROPOXYLATED NEOPENTYL GLYCOL **OECD 429**

DIACRYLATE Result: sensitising

Severity: EC3=4,6% OECD 429, LLNA

HEXAMETHYLENE DIACRYLATE (HDDA)

Result: sensitising Species: Mouse Severity: EC3 = 0,9% Result: sensitising

Trimethylolpropane triacrylate

Species: Human Result: sensitising Species: Human

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Germ cell mutagenicity: Ames test

(5-Ethyl-1,3-dioxan-5-yl)methyl acrylate **OECD 471**

Result: Negative.

Ethyl 4-dimethylaminobenzoate **OECD 471**

Result: Negative.

Phenylbis(2,4,6-trimethylbenzoyl) phosphine-oxide **OECD 471**

Result: Negative.

PROPOXYLATED NEOPENTYL GLYCOL

OECD 471

DIACRYLATE

Result: Negative.

DI(TRIMETHYLOLPROPANE) TETRAACRYLATE

OECD 471 Result: positive

HEXAMETHYLENE DIACRYLATE (HDDA)

OECD 471, In vitro Result: Negative

Trimethylolpropane triacrylate

OECD 471. In vitro Result: Negative

Ethyl 4-dimethylaminobenzoate

Germ cell mutagenicity: Chromosome abberation

OECD 471, without metabolic activation.

Phenylbis(2,4,6-trimethylbenzoyl) phosphine-oxide

Result: Negative. **OECD 473**

Result: Negative. OECD 473, In vitro

Trimethylolpropane triacrylate Ethyl 4-dimethylaminobenzoate

Result: positive OECD 473, with metabolic activation

Result: positive

Germ cell mutagenicity: Micronucleus

(5-Ethyl-1,3-dioxan-5-yl)methyl acrylate

OECD 474 Result: Negative.

DI(TRIMETHYLOLPROPANE) TETRAACRYLATE

OECD 474 Result: Negative.

Ethyl 4-dimethylaminobenzoate

OECD 474 Result: Negative.

PROPOXYLATED NEOPENTYL GLYCOL

Species: Mouse OECD 474, (similar product)

DIACRYLATE

Result: Negative.

Trimethylolpropane triacrylate

OECD 474, In vivo Result: Negative OECD 487, In vitro

HEXAMETHYLENE DIACRYLATE (HDDA)

Result: Negative

Mutagenicity

PROPOXYLATED NEOPENTYL GLYCOL

DIACRYLATE

OECD 467 Result: Negative. **OECD 476**

(5-Ethyl-1,3-dioxan-5-yl)methyl acrylate HEXAMETHYLENE DIACRYLATE (HDDA)

Result: Negative. **OECD 476** Result: Negative.

Phenylbis(2,4,6-trimethylbenzoyl) phosphine-oxide

OECD 476 Result: Negative.

Trimethylolpropane triacrylate

OECD 476, In vitro Result: positive OECD 489. In vivo Result: Negative

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Reproductive toxicity

Carcinogenicity

May damage fertility or the unborn child.

Material name: UVgel 460 ink Black

SDS LIK 1965C041AA Version #: 1.3 Revision date: 27-September-2019 Issue date: 15-March-2019 8 / 14

Developmental effects

OECD 414 (5-Ethyl-1,3-dioxan-5-yl)methyl acrylate

Result: Negative. Species: Rat

Phenylbis(2,4,6-trimethylbenzoyl) phosphine-oxide

OECD 414 Result: Negative.

Trimethylolpropane triacrylate

Species: Rat **OECD 422** Result: Negative Species: Rat

Fertility effects - Males

Ethyl 4-dimethylaminobenzoate

OECD 421

Result: Adverse effects for fertility

Species: Rat Organ: Testes

Fertility effects - Males and females

PROPOXYLATED NEOPENTYL GLYCOL DIACRYLATE

OECD 421 Result: Negative.

Reproductivity

PROPOXYLATED NEOPENTYL GLYCOL DIACRYLATE

OECD 421 Result: Negative.

Trimethylolpropane triacrylate

OECD 422 Result: Negative Species: Rat

(5-Ethyl-1,3-dioxan-5-yl)methyl acrylate

OECD 422 Result: Negative.

HEXAMETHYLENE DIACRYLATE (HDDA)

OECD 422 Result: Negative. Species: Rat

DI(TRIMETHYLOLPROPANE) TETRAACRYLATE

OECD 422, Read across Result: Negative. Species: Rat

Specific target organ toxicity -Not classified.

single exposure

Specific target organ toxicity -

Not classified.

repeated exposure

PROPOXYLATED NEOPENTYL GLYCOL DIACRYLATE

OECD 407 Result: Negative. Species: Rat

HEXAMETHYLENE DIACRYLATE (HDDA)

OECD 422 Result: Negative. Species: Rat

Phenylbis(2,4,6-trimethylbenzoyl) phosphine-oxide

Result: Negative. Species: Rat Test Duration: 90 d

Aspiration hazard Mixture versus substance

Not an aspiration hazard. No information available.

information

Other information

Not available.

SECTION 12: Ecological information

Toxic to aquatic life with long lasting effects. 12.1. Toxicity

Components **Species Test Results**

(5-Ethyl-1,3-dioxan-5-yl)methyl acrylate (CAS 66492-51-1)

Aquatic

Acute

EC50 34 mg/l, 72 h Algae Algae Crustacea LC50 20 mg/l, 48 h Daphnia LC50 Fish 4 mg/l, 96 h

DI(TRIMETHYLOLPROPANE) TETRAACRYLATE (CAS 94108-97-1)

Aquatic

Acute

Algae EC50 Algae 12 mg/l, 72 h Crustacea EC50 Daphnia > 10 mg/l, 48 h Fish EC50 Fish 1.2 mg/l, 96 h

Material name: UVgel 460 ink Black

SDS UK 1965C041AA Version #: 1.3 Revision date: 27-September-2019 Issue date: 15-March-2019

Test Results Components **Species** Ethyl 4-dimethylaminobenzoate (CAS 10287-53-3) Aquatic Acute Algae EC50 Algae 2.8 mg/l, 72 h LC50

HEXAMETHYLENE DIACRYLATE (HDDA) (CAS 13048-33-4)

LC50

Aquatic

Crustacea

Acute

Fish

EC50 Algae Algae 1.5 mg/l, 72 h Crustacea LC50 Daphnia 2.6 mg/l, 48 h LC50 Fish Fish 0.38 mg/l, 96 h

Daphnia

Fish

Chronic

NOEC Algae 0.5 mg/l, 21 d Algae **NOEC** Crustacea Daphnia 0.14 mg/l, 21 d

Phenylbis(2,4,6-trimethylbenzoyl) phosphine-oxide (CAS 162881-26-7)

Aquatic

Acute

Algae EC50 0.26 mg/l, 72 h Supersaturated Algae

suspension

31.8 mg/l, 48 h

1.9 mg/l, 96 h

Crustacea LC50 Daphnia 1.1 mg/l, 48 h Supersaturated

suspension

Fish LC50 Fish > 90 µg/l, 96 h Supersaturated

suspension

Chronic

Crustacea NOEC Crustacea 8.1 µg/l, 21 d

PROPOXYLATED NEOPENTYL GLYCOL DIACRYLATE (CAS 84170-74-1)

Aquatic

Acute

Algae EC50 Algae 3.4 mg/l, 72 h LC50 37 mg/l, 48 h Crustacea Daphnia Fish LC50 Fish 2.7 mg/l, 96 h

Trimethylolpropane triacrylate (CAS 15625-89-5)

Aquatic

Acute

EC50 Algae Algae 4.9 - 14.5 mg/l, 96 h Crustacea EC50 Invertebrates (Invertebrates) 19.9 mg/l, 48 h Fish LC50 Fish 0.87 mg/l, 96 h

12.2. Persistence and

degradability

Biodegradability

Percent Degradation (Aerobic Biodegradation)

(5-Ethyl-1,3-dioxan-5-yl)methyl acrylate OECD 301B

Result: 28

OECD 301B, Not readily biodegradable Ethyl 4-dimethylaminobenzoate

Result: 40

HEXAMETHYLENE DIACRYLATE (HDDA) 60 - 70 % OECD 310

PROPOXYLATED NEOPENTYL GLYCOL DIACRYLATE Result: Inherently biodegradable

12.3. Bioaccumulative potential

Partition coefficient

n-octanol/water (log Kow)

(5-Ethyl-1,3-dioxan-5-yl)methyl acrylate > 1.9

HEXAMETHYLENE DIACRYLATE (HDDA) 2.81, Log Kow

Phenylbis(2,4,6-trimethylbenzoyl) phosphine-oxide 5.8

PROPOXYLATED NEOPENTYL GLYCOL DIACRYLATE 2.41 - 3.87, Log Kow

Trimethylolpropane triacrylate > 3.3 **Bioconcentration factor (BCF)**

DI(TRIMETHYLOLPROPANE) TETRAACRYLATE 388 % v/w Phenylbis(2,4,6-trimethylbenzoyl) phosphine-oxide < 5

No data available. 12.4. Mobility in soil

Adsorption

Soil/Sediment Sorption - Log Koc

Ethyl 4-dimethylaminobenzoate Result: 2,8 HEXAMETHYLENE DIACRYLATE (HDDA) 2.1 3.85 Phenylbis(2,4,6-trimethylbenzoyl) phosphine-oxide 2 24 Trimethylolpropane triacrylate

12.5. Results of PBT and vPvB

Not a PBT or vPvB substance or mixture.

assessment

12.6. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Disposal Considerations: EU waste codes

16 02 13* - discarded equipment containing hazardous components other than those mentioned in

16 02 09 to 16 02 12

EU waste code

waste ink containing hazardous substances 08 03 12*

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 14.2. UN proper shipping

((5-Ethyl-1,3-dioxan-5-yl)methyl acrylate, Trimethylolpropane triacrylate) name

14.3. Transport hazard class(es)

Class 9 Subsidiary risk 9 Label(s) 90 Hazard No. (ADR) Tunnel restriction code Ε 14.4. Packing group Ш 14.5. Environmental hazards Yes

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

RID

14.1. UN number UN3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 14.2. UN proper shipping

((5-Ethyl-1,3-dioxan-5-yl)methyl acrylate, Trimethylolpropane triacrylate) name

14.3. Transport hazard class(es)

Class 9 Subsidiary risk 9 Label(s) Ш 14.4. Packing group 14.5. Environmental hazards

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

ΔDN

14.1. UN number UN3082

14.2. UN proper shipping ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

((5-Ethyl-1,3-dioxan-5-yl)methyl acrylate, Trimethylolpropane triacrylate) name

Material name: UVgel 460 ink Black

14.3. Transport hazard class(es)

Subsidiary risk 9 Label(s) 14.4. Packing group Ш 14.5. Environmental hazards Yes

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

IATA

14.1. UN number UN3082

Environmentally hazardous substance, liquid, n.o.s. ((5-Ethyl-1,3-dioxan-5-yl)methyl acrylate, 14.2. UN proper shipping

TRIMETHYLOLPROPANE TRIACRYLATE)

14.3. Transport hazard class(es)

9 Class Subsidiary risk 14.4. Packing group Ш 14.5. Environmental hazards Yes **ERG Code**

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

Other information

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN3082 14.1. UN number

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 14.2. UN proper shipping

((5-Ethyl-1,3-dioxan-5-yl)methyl acrylate, TRIMETHYLOLPROPANE TRIACRYLATE), MARINE name

POLLUTANT

Not established.

14.3. Transport hazard class(es)

Class 9 Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards Marine pollutant

Yes F-A. S-F **EmS**

14.6. Special precautions


for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Code

ADN; ADR; IATA; IMDG; RID



Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at

work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as

amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations Not available.

References Not available.

Information on evaluation

method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under

not written out in full under

Revision information

Sections 2 to 15 H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

This document has undergone significant changes and should be reviewed in its entirety.

Training information Follow training instructions when handling this material.

1965C041AA Version #: 1.3 Revision date: 27-September-2019 Issue date: 15-March-2019

Material name: UVgel 460 ink Black

Disclaimer

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation and is believed to be accurate. It provides guidance on health, safety and environmental aspects of the product and should neither be construed as any guarantee of specific properties nor of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1. This document was prepared to the requirements of the jurisdiction in Section 1 and may not meet regulatory requirements in other countries or territories. The information contained in this safety data sheet does not replace the user's own assessment of workplace risks, as required by applicable health and safety legislation.

Material name: UVgel 460 ink Black

SDS UK